



NO OF CONTACT	A±0.2	B±0.2	C±0.2	D±0.2	E±0.2	F±0.2
20	15.24	15.24	5.08	5.08	16.70	12.70
28	17.78	17.78	7.62	7.62	20.30	15.24
32	18.20	20.74	7.62	10.16	22.76	17.78
44	23.28	23.28	12.70	12.70	28.05	20.32
52	25.74	25.74	15.24	15.24	31.13	22.86
68	30.82	30.82	20.32	20.32	38.31	27.94
84	35.90	35.90	25.40	25.40	45.50	33.02

P.C.B LAYOUT

Insulator Material: PPS&40% Glass Fiber (UL 94-V0)
 Contact Resistance: 30MΩ Max at Dc 100ma
 Insulator Resistance: 1000MΩ Min at Dc 500V
 Current Rating: 1AMP
 Dielectric Withstand Voltage: AC 500V for 1 minute
 Temperature Rating: -55 deg C ~+ 105 deg C
 Contact Material: Phosphor Bronze

SECTION A-A

易昕企業有限公司 LEAMAX ENTERPRISE CO., LED.					
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 2111-T1E		
APP	JAMES	100.09.07	MODEL	FILE NO	REV.
CHK	CCJ	89.11.30	ROHS	WITH PEG	X3
DGN	WU	89.11.30	UNIT	SHT 1 OF 1	SIZE
DRW	SHIEH	89.11.30	MM		A4