


Specifications:

Current rating:3.0A AC/DC
 Voltage rating:100V AC/DC
 Contact resistance:10m ohm. max.
 Insulator resistance:5000M ohm. Min.
 Withstanding voltage:1000V AC for one minute
 Operating temperature range:-40°C to +105°C
 Material and Finish:
 Insulator:High Temp. Plastic(PPS UL94V-0)
 Standard Color:Black
 Contact:Beryllium Copper(Becu) Gold Plated
 Sleeve Barrel:Brass Tin Plated


ORDER INFORMATION

2 1 5 0 - x x E



Dimension:


Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B
2	5.08	2.54	12	30.48	27.94	22	55.88	53.34	32	81.28	78.74
3	7.62	5.08	13	33.02	30.48	23	58.42	55.88	33	83.82	81.28
4	10.16	7.62	14	35.56	33.02	24	60.96	58.42	34	86.36	83.82
5	12.70	10.16	15	38.10	35.56	25	63.50	60.96	35	88.90	86.36
6	15.24	12.70	16	40.64	38.10	26	66.04	63.50	36	91.44	88.90
7	17.78	15.24	17	43.18	40.64	27	68.58	66.04	37	93.98	91.44
8	20.32	17.78	18	45.72	43.18	28	71.12	68.58	38	96.52	93.98
9	22.86	20.32	19	48.26	45.72	29	73.66	71.12	39	99.06	96.52
10	25.40	22.86	20	50.80	48.26	30	76.20	73.66	40	101.60	99.06
11	27.94	25.40	21	53.34	50.80	31	78.74	76.20			



PCB Layout

RoHS Compliant

E				APP Chen 21-10-15	GENERAL TOLERANCE: X.X=±0.2 X.XX=±0.15
D				CHK Huang 01-09-15	UNIT: MM
C				DRW P. D. J 04-03-08	SCALE:
B	23-02-11	ECN-CN1102006	Richie		SHEET: 1 / 1
A	04-03-08	(PC0154)	P.D.J		PROJECTION:
REV	DATE	FILE	BY		



易昕企業有限公司
LEAMAX ENTERPRISE CO., LTD.

TITLE:
2.54mm Machine Pin Socket Single Row

DWG NO. 2150-001

SIZE
A4