



SPECIFICATIONS

MATERIAL:

- 1. Insulator : PBT Polyester UL 94-V0
- 2. Color : Black
- 3. Contacts : SQ 0.64mm Gold/Tin Selective Plated

ELECTRICAL:

- 1. Current Rating : 1.0 Amps
- 2. Operation Temperature : $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 3. Contact Resistance : 10 m ohms max
- 4. Insulation Resistance : 1000M Ω min
- 5. Dielectric Withstanding : 500V AC

POS	DIM		
	A	B	C
6	15.24	12.94	5.08
8	17.78	15.48	7.62
10	20.35	18.01	10.16
12	22.86	20.56	12.70
14	25.40	23.10	15.24
16	27.94	25.64	17.78
20	33.05	30.75	22.86
24	38.72	35.92	27.94
26	40.76	38.46	30.48
30	45.84	43.54	35.56
34	51.15	48.90	40.64
40	58.67	56.24	48.26
44	63.62	61.32	53.34
50	71.24	68.94	60.96
60	84.00	81.40	73.66
64	89.04	86.74	78.74

Order Information

PART NO. 2 1 7 0 x x x E
 No of contacts
 TYPE:
 S: Straight Type
 R: RIGHT ANGLE
 RoHS

易昕企業有限公司 LEAMAX ENTERPRISE CO., LTD.			
PROJ		SCALE : F DO NOT SCALE DWG	DWG NO.2170-001
GENERAL TOLERANCE	APP	28-06-16	TITLE
± 0.25	CHK	18-11-14	BOX HEADER 2.54mm
	DRW	22-01-02	REV. X5
			UNIT MM
			SHT 1 OF 1
			SIZE A4