



	1	2	3	4	5	6	7
						A	B
						C	D
						E	
Positions	±0.25	±0.20	±0.38	±0.25	±0.25		
09	16.30	25.00	30.80	19.15	16.90		
15	24.60	33.30	39.20	27.60	25.25		
25	38.35	47.05	53.05	41.10	38.95		
37	54.80	63.50	69.40	57.40	55.40		

Order Information
3222-xxSxxxGE

Position _____
 S: Straight Type _____
 M: MALE _____
 S: FEMALE _____

MOUNTING OPTION

1: CODE 1
 2: CODE 2
 3: CODE 3
 4: CODE 4
 5: CODE 5
 6: CODE 6

RoHS _____
 Contact Plating _____
 G: Gold Plated _____
 Housing Color _____
 B: BLACK PBT _____
 W: White PBT _____
 L: BLUE PBT _____

SPECIFICATIONS

Insulator : PBT+30% glass fiber , UL 94V-0
 Contact : Brass or Phosphor bronze
 Current rating (Max) : 3amp AC / DC
 Withstanding voltage : 1000 VAC
 Insulation resistance (Min.):1000M Ω
 Contact resistance (Max):15m Ω
 Operating temperature : -55°C~+105°C

LEAMAX 易昕企業有限公司
 LEAMAX ENTERPRISE CO., LTD.

PROJ	SCALE : F DO NOT SCALE DWG	TITLE D-SUB PCB STRAIGHT TYPE STAMPED CONTACT		
APP	Chen	11-08-15	DWG NO.3222-000	
CHK	Huang	03-08-15	UNIT	REV. XA
DRW	SHIEH	01-11-00	MM	SHT 1 OF 1
				SIZE A4