



1. 10 sprocket hole pitch cumulative tolerance ± 0.20 .
2. Carrier camber is within 1 mm in 250mm.
3. Material : Black Conductive Polystyrene Alloy (UP-5000).
4. All dimensions meet EIA-481-B requirements.
5. Thickness : 0.30 ± 0.05 mm.
6. Packing length per 22" reel : 36.0 Meters.
7. Component load per 13" reel : 350 pcs.

Patent No. 157713

W	44.00±0.30
A0	23.80±0.10
B0	23.80±0.10
K0	5.60±0.10
K1	4.90±0.10

 易昕企業有限公司 <i>Leamax Enterprise Co., Ltd.</i>	Customer No. : 211144TTE	Approved : _____	UPAK No. PLSK-44									
	DESCRIPTION : ECE	Checked : <i>James Chen</i>	Drawn : <i>Amy Shen</i> 07/06/2006		<table border="1" style="font-size: small;"> <thead> <tr> <th>UNIT</th> <th>SCALE</th> <th>SHEET</th> <th>REV.</th> </tr> </thead> <tbody> <tr> <td>mm</td> <td>1.5 : 1</td> <td>1 / 1</td> <td>A</td> </tr> </tbody> </table>	UNIT	SCALE	SHEET	REV.	mm	1.5 : 1	1 / 1
UNIT	SCALE	SHEET	REV.									
mm	1.5 : 1	1 / 1	A									