



NO .OF CONDECTOR	Width(mm)	Compositlon(mm)	Allowable error
9P	11.43	7/0.127	±0.30
10P	12.70	7/0.127	±0.30
15P	19.05	7/0.127	±0.30
20P	25.40	7/0.127	±0.30
25P	31.75	7/0.127	±0.30
34P	43.18	7/0.127	±0.40
40P	50.80	7/0.127	±0.40
50P	63.50	7/0.127	±0.40
60P	76.20	7/0.127	±0.40
64P	81.28	7/0.127	±0.40

Shell Size	A	B	C	D
	±0.20 ±0.006	±0.10 ±0.004	±0.10 ±0.004	±0.10 ±0.004
6P	12.10/0.480	8.50/0.335	5.08/0.200	6.35/0.250
8P	14.72/0.580	11.04/0.435	7.62/0.300	8.89/0.350
10P	17.40/0.685	13.60/0.535	10.16/0.400	11.43/0.450
12P	19.80/0.780	16.05/0.633	12.70/0.500	13.97/0.550
14P	22.45/0.864	16.65/0.734	15.24/0.600	16.51/0.650
16P	25.08/0.957	21.22/0.835	17.78/0.700	19.05/0.750
20P	30.20/1.189	26.30/1.035	22.86/0.900	24.13/0.950
24P	35.04/1.189	31.30/1.232	29.74/1.100	29.21/1.150
26P	37.70/1.484	33.04/1.332	30.48/1.200	31.75/1.250
30P	42.70/1.681	38.90/1.531	35.56/1.400	36.83/1.450
34P	47.84/1.883	44.05/1.734	40.64/1.600	44.91/1.650
40P	55.58/2.188	51.68/2.035	48.26/1.900	49.53/1.950
50P	68.14/2.662	64.32/2.532	60.96/2.400	62.23/2.450
60P	81.01/3.191	77.20/3.040	73.66/2.900	74.93/2.950
64P	85.64/3.780	82.14/3.234	78.74/3.100	80.01/3.150

Construction drawing  
 NO28 awg 7x0.12 linned  
 Strand fo copper conucror

POLARLY MARK  
 P1+1.27±0

MATERIAL  
 CONTACT:PHOSPHOR BRONZE GOLD FLASH OVER NICKEL  
 INSULATOR:P.B.T &GLASS-FINER RCINFORCED UL94V-0

SPECIFICATION  
 CONTACT RATING: 2.54mm grid  
 NO.OF CONTACTS: 6,8,10,12,14,16,20,24,26,30,34,40,50,60,64  
 Current Rating: 1 Amps DC  
 CONTACT RESISTANCE: 30m ohms Max at 6v DC 0.3A  
 Insulator resistance 1000M ohms Min at 500 DC  
 Operating Temperature: -55°C~+105°C  
 DIELECTRIC WITHSTARING VOLTAGE: 500V AC for one minute  
 SIRE SIZE FLAT CABLE 1.27mm spacing AWC#20(standard) or 30(solid)  
 I.D.C:

**易昕企業有限公司**  
 LEAMAX ENTERPRISE CO., LED.

PROJ	SCALE : F DO NOT SCALE DWG	MOLD NO	8752		
APP		MODEL	FILE NO	REV.	X1
CHK	CCJ	90.08.09			
DGN	AMY	90.08.09	UNIT	SHT 1 OF 1	SIZE
DRW	SHIEH	90.08.09	MM		A4