



NO.OF PIN	DIM		
	C	B	A
2	4.25	3.15	1.25
3	5.50	4.40	2.50
4	6.75	5.65	3.75
5	8.00	6.90	5.00
6	9.25	8.15	6.25
7	10.50	9.40	7.50
8	11.75	10.65	8.75
9	13.00	11.90	10.00
10	14.25	13.15	11.25
11	15.50	14.40	12.50
12	16.75	15.65	13.75
13	18.00	16.90	15.00
14	19.25	18.15	16.25
15	20.50	19.40	17.50

MATERIAL:
 WAFER:HIGH TEMPERA TURE PLASTIC
 NYLON46 UL94V-0
 PIN:HIGH STRENGTH BRASS
 WITH TIN OVER NICKET PLATED

SPECIFICATION:
 CURRENT RATE:1AMP
 INSULATION RESISTANCE:500M MIN
 CONTACT RESISTANCE:20M MAX
 DIELECTRIC VOLTAGE:500V AC FOR ONE MINUTE
 OPERATION TEMPERATURE:-25°C~+85°C

 易昕企業有限公司 LEAMAX ENTERPRISE CO., LED.					
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 4318DxxSE		
APP	AMY	98.04.13	MODEL	FILE NO	REV.
CHK	CCJ	91.05.15	WITHOUT EAR	wire to board 1.25mm WAFER DIP 180°	X1
DGN	AMY	91.05.15	UNIT	SHT 1 OF 1	SIZE
DRW	SHIEH	91.05.15	MM		A4