



REV	MODIFICATION	DATE	DRAW
B1	Release To ECN20141106	21-11-14	Michelle
B2	Release To ECN20140805	05-08-14	Michelle
B3	Release To ECN20160104	20-01-16	Michelle

RoHS Compliant

Specification

1. Current Rating: 2A AC/DC
2. Voltage Rating: 100V AC/DC
3. Contact Resistance: 20mΩ Max.
4. Insulation Resistance: 1000MΩ Min. At DC500V
5. Dielectric Withstanding Voltage: AC800V/Minute
6. Operating Temperature: -25°C ~ +85°C

Material:

1. Housing: High Temperature Thermoplastic UL94V-0
2. Contact Pin: Copper Alloy SQ. Pin 0.50mm

Finish:

1. Housing: Nylon66 UL94V-0 Natural
2. Contact Pin: Bright Tin Plated Over Nickel With Kink

Part No.: **4320-xxKE**

No Of Contacts
02~16

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: Wire To Board Wafer 2.00mm 180° DIP Single Row With Kink			
.X ± 0.35	X. ° ± 2°	APP Chen 03-08-17	DWG NO. 4320-DK1			
.XX ± 0.25	.X. ° ± 1°	CHK Huang 01-08-17	UNITS: mm	PN: 4320-xxKE		
.XXX ± 0.15	.XX. ° ± 0.5°	DRA Michelle 20-01-16	SIZE: A4	SCALE 5:1	SHEET 1 / 1	REV B3 V



易昕企業有限公司
LEAMAX ENTERPRISE CO.,LTD.